

MAN TGX 18.440 4X2 LLS-U

SH04880724



Body type	Tractor unit
1st reg.	02/2017
Power	324kW (441 HP)
Mileage	706662 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGM
Model variant	TGM TG2
Body type	Tractor unit (Mega)
Colours	white
Driver's cab	XLX
Berths	2 berths

TECHNICAL DATA

Power	324 kW (441 HP)
Fuel	Diesel
Gearbox type	Semiautomatic
Wheel drive	4x2
Suspension	Air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 80 l Fuel tank: 480 l Fuel tank: 480 l
Emission category	Euro6

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Comfort

- Adjustable steering column
- Electric window lift 2x
- Air conditioning
- Driver's armrest
- Front seats adjustable in height
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Isolated driver's cab
- DC/AC converter

Interior

- Board computer
- Multifunctional steering wheel
- Digital tachograph
- Carpet floor covering
- Cooling box

Light and sight

- Fog lights
- Tinted glass
- Cornering light
- Daytime running lights

Exterior

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- Fifth wheel
- 1x15 pin plug
- Working lights
- Lifting roof (manual)
- Telematics system

Audio & communication

- Radio
- Mobile phone preparation Bluetooth
- AUX & USB connector

Assistance systems

- Efficientcruise
- MAN BrakeMatic
- Brake assist: Emergency Brake Assist 2

- Lane-Guard-System LGS
- Hill Hold Control HHC
- Speed limiter

Wheels and tyres

- Spare wheel carrier

Equipment packages

- Aero package
- Efficientline 2 package

Others

- front air suspension 7.5 t, rear air suspension 11.5 t, hub reduction rear axle Hypoid HY-1350, hypoid axle ratio i 2.53, fuel filter heating, cab insulation NORDIC, cross member for trailer coupling, wiring for tank truck to ADR, ADR Typ AT, equipment for dangerous goods to ADR, type OX, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (15-pin)