MAN

MAN TGX 18.440 4X2 BLS

SH05820924



Price **15,400 EUR** (net)

18,634 EUR (gross)

Offer Date 20.10.2025

Body type Tractor unit
1st reg. 10/2015

Power 324kW (441 HP)

Mileage 797574 km

Storage location Otopeni - MHS Truck

Service

BASIC DATA

Brand MAN

Model serie TGS

Model variant TGS TG2

Body type Tractor unit (Standard)

Colours white
Driver's cab XLX
Berths 1 berth

TECHNICAL DATA

Power 324 kW (441 HP)

Fuel Diesel
Gearbox type Manual
Wheel drive 4x2

Suspension Leaf air suspension

Axles 2 axles

WEIGHTS AND MEASURES

GVW 18,000 kg
Rear overhang 800 mm
Wheel base 3600 mm

Fuel tank AdBlue: 60 I

Fuel tank: 400 l

Emission category Euro6



EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Interior

- Board computer
- Multifunctional steering wheel
- Digital tachograph
- Sun visor
- Carpet floor covering

Audio & communication

- Radio/CD
- AUX & USB connector

Light and sight

- Tinted glass
- Headlight range control
- Daytime running lights

Others

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Driver's armrest
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Isolated driver's cab
- DC/AC converter

Exterior

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Roof spoiler
- Low noise
- Rear differential lock
- PTO
- Fifth wheel
- Spare wheel
- Cab Suspension
- Lifting roof (manual)
- Telematics system

Assistance systems

- Cruise control
- MAN BrakeMatic
- Speed limiter

Wheels and tyres

Spare wheel carrier



front springs parabolic 7.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, HY axle ratio i 2.71, fuel filter heating, cab insulation NORDIC, wiring for tank truck to ADR, ADR Typ AT, equipment for dangerous goods to ADR, type OX, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (7-7-pin), pick-up plate 40 mm